



Technical Specifications:

Output power continous sinewave:	105W/8Ω	170W/4Ω	0.1% THD
Output power pulsed:	350W/2Ω	410W/1Ω	0.1% THD
Maximum continous current:	6A		
Maximum Pulsed current:	20A (100ms burst)		
Distortion THD:	0.0127% 8Ω – 5Watt – 1Khz		
Distrortion TIM:	0.014% 8Ω – 5Watt – 50Hz/7Khz 4:1		
Hum and Noise level:	-97.9dB ref: Max, output level		
Bandwith:	DC – 127Khz -3dB 1W/8Ω		
Gain max:	100x = 40dB 280mV for max output		
Input impedance:	47KΩ		
Damping factor:	600		
Slew rate:	19V/uS		
AC voltage:	115VAC / 230VAC internal switch 50/60Hz +/-10%		
Power consumption:	Idle 9VA – Max 550 VA		
Powersupply:	500VA torroid and 6x10.000uf		
Volume controll:	64 step Log digital controlled ladder switch		
Features:	Each outputchannel programmable output gain (-6dB) Programmable switch 2channel to 4 channel mode Programmable switch 2 channel with sub out mode Poweramplifier on L+R, other channels pre-out only Infrared remotecontrol		
Protection:	Internal Fuse on powerrail only (no current limiting) Poweramp mute on switch off		
Inputs:	2x6channel + 4x2channel line input RCA gold plated		
Outputs:	4channel pre out + 2channel rec out RCA gold plated		
Controlls:	1x rotary encoder + 10 push button		
Loudspeaker outputs:	2x Binding post gold plated		
Dimensions:	440x98(108)x375mm WxH(with feet)xD		

april 2006